



## CoilSTREAM VB 3283 VISCOSITY BUILDER

CoilSTREAM VB 3283 is a superior viscosity builder designed as a gel sweep for the frac plug coiled tubing/ stick pipe drill out application. Chemstream’s CoilSTREAM VB 3283 is a synthetic polymer that builds viscosity and is used as a thickening agent for in frac plug drill outs. CoilSTREAM VB 3283 excels in building sweep viscosity in heavily produced flow back water as well as heavy brines. CoilSTREAM VB 3283 also has friction reduction capabilities and will help lower circulating pump pressures for coil tubing as well as work over units. CoilSTREAM VB 3283 hydrates rapidly and does not need time or fresh water to fully hydrate.

### Application

CoilSTREAM VB 3283 suspends sand and solids during drill outs. This product brings well bore debris and plugs parts to surface in all types of water.

CoilSTREAM VB 3283 is the best gelling agent to use in all intervention work overs.

### Dosage

|                                             |               |
|---------------------------------------------|---------------|
| 2 1/2 Gallons per 10 bbls of produced water | 65 Viscosity  |
| 5 Gallons per 10 bbls of produced water     | 95+ Viscosity |

### Benefits

- Builds viscosity in all types of water
- Helps lower circulating pressures
- Appalachian Basin Tested for building viscosity
- Easy to Handle in theField
- Pours well in cold weather

### Compatibility

Because of its ionic character, CoilSTREAM VB 3283 is compatible with the fluid systems and additives used in the frac plug drill out process. This product has been shown to have negligible impact on gel, cross-linked, gel, FR, and lube systems.

### Handling/Storage

Store in a cool, dry, well ventilated and shaded area, away from heat sources and incompatible materials. To maintain product quality, store product at temperatures below 104°F (40°C). Refer to the Safety Data Sheet (SDS) for handling and hazard data.

### Physical Properties

Appearance ..... Clear to white  
 Odor ..... Mild oily  
 Specific Gravity..... 1.04  
 Product Density ..... 8.83 lb./gal  
 Flash Point ..... >215°F  
 Boiling Point ..... N.A.  
 Freezing Point..... < 10°F  
 pH (neat) .....6.0 - 9.0  
 Solubility ..... Dispersible in water  
 Chemical Family.....Synthetic Polymer

### Ordering Information

Available in 5 gallon buckets or totes.  
 Contact information is below.

**Call us at 724-915-8388, or visit us on the web at [www.chemstream.com](http://www.chemstream.com)**

**511 Railroad Avenue, Homer City, PA 1574 | Office 724-915-8388 | Fax 724-915-8374**

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user’s specific application. Chemstream does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing about the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, about the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.