



CoilSTREAM VB 746 VISCOSITY BUILDER

CoilSTREAM VB 746 is a synthetic polymer that builds viscosity and is used as a thickening agent for in frac plug drill outs. CoilSTREAM VB 746 excels in building sweep viscosity in heavily produced flow back water as well as production brines. It continues to build viscosity as you add more polymer. Chemstream's CoilSTREAM VB 746 can be used as a friction reducer for coil tubing and work over applications. CoilSTREAM VB 746 hydrates rapidly in heavily produced high brine water, as well as in acid.

CoilSTREAM VB 746 hydrates rapidly and does not need time or fresh water to fully hydrate. CoilSTREAM VB 746 suspends sand and solids during drill outs. This product brings well bore debris and plugs parts to surface in all types of water. CoilSTREAM VB 746 is the best gelling agent to use in all intervention work overs.

Dosage

2 1/2 Gallons per 10 bbls of produced water	70 Viscosity
5 Gallons per 10 bbls of produced water	100+ Viscosity

Benefits

CoilSTREAM VB 746 is a suspension of polymer in an iso-alkane oil.

- Builds viscosity in all types of water rapidly and under adverse field and water conditions
- Helps lower circulating pressures as it builds viscosity
- Easy to handle in the field
- Pours well in cold weather
- Available in 5 gallon buckets or totes
- Appalachian Basin Tested for building viscosity

Compatibility

Because of its ionic character, CoilSTREAM VB 746 is compatible with the fluid systems and additives used in the frac plug drill out process. This product has been shown to have negligible impact on gel, crosslinked, gel, FR, and lube systems.

Handling/Storage

Store in a cool, dry, well ventilated and shaded area, away from heat sources and incompatible materials. To maintain product quality, store product at temperatures below 104°F (40°C). Refer to the Safety Data Sheet (SDS) for handling and hazard data.

Physical Properties

Appearance	White liquid
Odor	Mild hydrocarbon
Specific Gravity	0.96
Product Density	8.01 lb./gal
Flash Point	>215°F
Boiling Point	433°F
Freezing Point	< 10°F
pH (neat)	7.0
Solubility	Dispersible in water
Chemical Family	Synthetic Polymer

Ordering Information

Available in 5 gallon buckets or totes

Dave Grottenthaler	412-999-2049
Jerry Berringer	724-787-2302
Keith Houseknecht	570-447-1283

Call us at 877-671-1694, or visit us on the web at www.chemstream.com

511 Railroad Avenue, Homer City, PA 15748 | 877-671-1694 | Office 724-915-8388 | Fax 724-915-8374

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chemstream does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing about the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, about the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.